










۸۲	۸۲	۸		
DESIGN REVIEW	OWNER REVIEW	BID PERMIT SET		
3.9.11	3.24.11	4.15.11		
				1






















LEGEND
























COLUMENT Y. ROOM TO THE CALL T	DEPENDENCE PLAZA  Not Atlantic Ave Total Atlantic Ave Alameda, CA





9. ALL DOORS IN ACCESSIBLE AREAS SHALL HAVE 1/2" MAX. HI THRESHOLD ABOVE FLOOR AND/OR LANDING ON BOTH SIDES. CHANGES IN ELEVATION BETWEEN 1/4" AND 1/2" SHALL BE BEVELED WITH A VERTICAL TO 2 UNITS HORIZONTAL. 11. ALL DOORS SHALL BE EQUIPPED WITH SINGLE-EFFORT, NON-GRASP HARDWARE CENTERED BETWEEN 30" AND 44" ABOVE THE FLOOR (UNLESS OTHERWISE NOTED), 10. ALL DOORS IN ACCESSIBLE AREAS SHALL HAVE MAXIMUM DOOR OPENING EFFORT OF 5 LB., AND 15 LB. AT FIRE DOORS (IF ALLOWED BY THE LOCAL AUTHORITY).

12. REFER TO DOOR AND WINDOW DRAWING DETAILS PER ORIGINAL 1993 DRAWINGS













3 AB.1 SIM.  AB.1 TYP.  ALUM. FRAME,  AWNING
3'-6" ALUM. FRAME, AWNING
امن اا ہے ا من

3'-0" A6.1 TYP.	3 A6.1 SIM.	AE.1 TYP. (C) ALUM FRAME, FIXED
3 TYP. 4 3'-0"	66.1 SIM.	ALUM. FRAME, AWNING
<b>†</b>	0-, <b>S</b>	<b>∤</b>      <u> </u>









A5.0

SCALE 1/8" = 1'-0"

KD PROJ. NO.
2.1010


SCHEDULES

FINISH

WINDOW,

DOOR,

3.9.11 DESIGN REVIEW





DOOR MATERIAL: SC: SOLID CORE WOOD HM: HOLLOW METAL

FRAME MATERIAL: WD.: WOOD H.M.: HOLLOW METAL

(3)

"8-'9

..レ-.Þ

FLUSH W/ VIEW PANEL

Ö.

1. DOORS SHALL BE OPERABLE FROM THE INSIDE WITHOUT THE USE OF A KEY, SPECIAL KNOWLEDGE OR EFFORT (UNLESS OTHERWISE NOTED), AND SHAL PUSH-PULL ACTIVATING BARS OR OTHER HARDWARE TO PROVIDE PASSAGE.

4. VERIFY ALL LOCKING, LATCHING AND KEYING REQUIREMENTS AND HARDWARE SPECIFICATIONS WITH OWNER PRIOR TO ORDERING AND INSTALLING HAI

3. INSTALL DOORS COMPLETE WITH ALL HARDWARE, FITTINGS AND ACCESSORIES AS REQUIRED FOR THE OPERATION OF THE SPECIFIC OPENING.

2. LEVER TYPE DOOR HANDLES SHALL HAVE RETURN WITHIN 1/2" TO DOOR.

A. SINGLE, FLUSH

5. UNDERCUT THE DOORS SO THAT THE BOTTOM OF THE DOOR IS 1/8" MINIMUM AND 1/4" MAXIMUM ABOVE THE FINISH FLOOR UNLESS NOTED OTHERWISE

8. VERIFY FRAME DIMENSIONS WITH WALL THICKNESS IN FIELD PRIOR TO ORDERING.

6. NOTED DOOR HEIGHTS ARE TO THE TOP OF THE DOOR.

7. VERIFY DOOR HEIGHTS WITH HEAD CONDITIONS.

FINISH: PTD: PAINTED STN: STAINED


(2)

"1-'S


DOOR SCHEDULE KEY NOTES

PAIR WHERE OCCURS 3'-0"

PAIR WHERE OCCURS



40 27 27



(N) STORAGE ON 2ND FL.

(N) MEETING ROOM ON 2ND FL.

(N) VESTIBULE ON 2ND FL.

(N) LARGE CONFERENCE RM. ON 2ND FL.

(N) VESTIBULE ON 2ND FL.

(N) STORAGE ROOM ON 2ND FL.
(E) BATHROOM ON 1ST FL.
(E) BATHROOM ON 1ST FL.
(E) BATHROOM ON 2ND FL.
(E) BATHROOM ON 2ND FL.

PTD. PTD. PTD.

**OEFICE BUILDING** 

(N) INTERVIEW ROOM ON 1ST FL.
(N) INTERVIEW ROOM ON 1ST FL.
(N) INTERVIEW ROOM ON 1ST FL.
(N) OFFICE ON 1ST FL.
(N) OFFICE ON 1ST FL.

REMARKS (6)

(2) EFEC

FIRE DNITAЯ

GROUP GROUP

DETAILS

FRAME

SCHEDULE

DOOR

SILL

JAMB

HEAD

SIZE HEIGHT THK.

WIDTH

**TYPE** 

DOOR NO.

DOOR

MAT'L.
(4)
wpF
wdF

(N) BATHROOM ON 1ST FL.
HALLWAY ON 1ST FL.

03 03 09 09

P. .

WDF WDF WDF

PTD.

PT 0.

GLASS GLASS GLASS GLASS

PTD.

(N) OFFICE ON 1ST FL. (N) OFFICE ON 1ST FL.

